

TURBO LEVO

4.799,00 €



Black / Dusty Lilac



Flo Red / Black



Navy / White Mountains / Black

Das neue Turbo Levo macht die fortschrittlichste E-MTB Rahmen-, Motor- und Batterietechnologie für alle erschwinglich. Wir haben unseren M5 Aluminium Rahmen und den kraftvollsten und geschmeidigsten Motor auf dem Markt und haben dies mit den Antriebs-, Brems- und Federungskomponenten kombiniert, die das beste Preis-Leistungs-Verhältnis haben. Dieses Bike stellt viele, viel teurere E-MTBs in den Schatten.

SPECS Technische Änderungen vorbehalten.

RAHMEN	Specialized M5 Premium Aluminum, 29 Trail Geometry, integrated down tube battery, enclosed internal cable, Command Post routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel
DÄMPFER	RockShox Deluxe Select w/ custom air valve, 52.5x210mm
GABEL	RockShox 35 29, DebonAir spring, Motion Control damper, 51mm offset, 15x110mm thru-axle
VORBAU	Specialized Trail, 3D-forged alloy, 4-bolt, 6-degree rise
LENKER	Specialized Trail, 6061 alloy, 8-degree backsweep, 6-degree upsweep, 27mm rise, 780mm, 31.8mm clamp
LENKERGRIFFE	Specialized Sip grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
BREMSE VORNE	SRAM Level T hydraulic disc, 4-Piston Caliper, 200mm
BREMSE HINTEN	SRAM Level T hydraulic disc, 2-Piston Caliper, 200mm
SCHALTWERK	SRAM NX, 11-speed
SCHALTHEBEL	SRAM S700, single-click lever
KASSETTE	SRAM PG-1130, 11-speed, 11-42t
KETTE	KMC X11ET, 11-speed w/ Missing Link™
KURBELGARNITUR	Praxis, 2D cold-forged alloy, custom offset, 165mm
KETTENBLÄTTER	32T, custom steel
FELGEN	Roval Traverse 29, hookless alloy, 30mm inner width, tubeless ready
VORDERRADNABE	Specialized, sealed cartridge bearings, 15x110mm thru-axle, 28h
HINTERRADNABE	Specialized, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPEICHEN	DT Swiss Industry
VORDERREIFEN	Butcher, GRID casing, GRIPTON® compound, 2Bliss Ready, 29x2.6"
HINTERREIFEN	Eliminator, BLCK DMND Casing, 2Bliss Ready, 29x2.3"
SATTEL	Body Geometry Myth 155 S, Body Geometry Henge 143 M/L/XL, steel rails
SATTELSTÜTZE	TranzX dropper, 34.9mm, XS-S: 100mm, M: 120mm, L/XL: 150mm Travel
MOTOR	Specialized 2.1, custom Rx Trail-tuned motor, 250W nominal
LENKERFERNBEDIENUNG	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
AKKU	Specialized M2-500, integrated battery w/rock guard, 500Wh
LADegerät	Custom charger, 42V4A w/ Rosenberger plug
KABELBAUM	Custom Specialized wiring harness
SWAT	Specialized Z-Cage w/EMT Cage Mount MTB Tool

TURBO LEVO	S	M	L	XL
Stack (mm)	606	606	634	647
Reach (mm)	415	435	455	480
Steuerrohrlänge (mm)	95	95	125	140
Steuerrohrwinkel (degrees)	66.04	66.04	66.04	66.04
Tretlagerhöhe (mm)	347.5	347.5	347.5	347.5
Tretlagerabsenkung (mm)	27	27	27	27
Nachlauf (mm)	111	111	111	111
Gabellänge, gesamt (mm)	560	560	560	560
Gabelversatz / Offset (mm)	51	51	51	51
Mitte Tretlager - Mitte V.-achse (mm)	729	749	781	812
Kettenstreben-Länge (mm)	455	455	455	455
Radstand (mm)	1182	1202	1235	1266
Oberrohrlänge horizontal (mm)	577	600	631	664
Überstandshöhe (mm)	760	760	781	787
Sitzrohrlänge (mm)	380	410	455	505
Sitzrohrwinkel (degrees)	75.04	74.79	74.48	74.14
Kurbellänge (mm)	165	165	165	165
Lenkerbreite (mm)	780	780	780	780
Vorbauhöhe (mm)	45	45	45	45
Sattellbreite (mm)	155	143	143	143
Länge Sattelstütze (mm)	406	456	456	456

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
95220-7302	LEVO 29 NB	Black / Dusty Lilac	S
95220-7303			M
95220-7304			L
95220-7305			XL
95220-7402	LEVO 29 NB	Flo Red / Black	S
95220-7403			M
95220-7404			L
95220-7405			XL
95220-7502	LEVO 29 NB	Navy / White Mountains / Black	S

TURBO LEVO

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
95220-7503	LEVO 29 NB	Navy / White Mountains / Black	M
95220-7504			L
95220-7505			XL