

TARMAC DISC

2.199,00 €



Gloss Flo Red/Metallic White Silver/Fine Silver/Tarmac Black

When we developed the Tarmac Disc, we didn't just want it to be fast. We wanted it to be fast everywhere. Long climbs, windy flats, Grand Tour stages, local fondos—we built a race bike to be the most complete out there. How'd we do it? We started with our Rider-First Engineered™ frame with a perfectly-tuned ride quality for every size, added in some serious aero tech that makes it 30 seconds faster than the Tarmac SL5 over 40 kilometers, and then made it 20% lighter. Nothing is lighter, faster, and better handling. This Tarmac comes with a reliable spec that includes 10-speed Shimano Tiagra mechanical shifting, quick-stopping hydraulic disc brakes, durable Axis Sport Disc wheels, and our fan-favorite Power saddle.

- For the construction of the Tarmac, we utilized advanced aerospace composite optimization software to revolutionize the construction and layout of our new FACT 8r carbon.
- 500 pieces creating 7 different sizes with the same tuned ride—that's Rider-First Engineered™. We examine every ply of carbon on every frame size to ensure that all of our performance targets come through. To make sure you get the perfect ride, every frame gets a unique layout schedule with different ply arrangements, orientations, quantities of material in specific areas, and sometimes, even exclusive thicknesses and types of carbon itself.
- Aerodynamics is the most important thing we can do to make you faster, but with the Tarmac, we added aero features without any cost to weight. Through development, areas were discovered where we could add aero for free—a new fork shape and dropped seatstays with aero tubes. The result? A Tarmac that's approximately 30 seconds faster over 40 kilometers.
- The updated the geometry is based on countless Retül data points and professional rider input. This enabled us to develop a Performance Road Geometry that perfects the combination of a responsive front-end and short wheelbase, which delivers instantaneous response and optimal power transfer.

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Tarmac SL6, FACT 9r carbon, Rider-First Engineered™, threaded BB, clean routing, 12x142mm thru-axle, flat-mount disc
GABEL	FACT 10r carbon, 12x100mm thru-axle, flat-mount disc
LENKER	Specialized Shallow Drop, 6061, 70x125mm, 31.8mm clamp
VORBAU	Specialized, 3D-forged alloy, 4-bolt, 7-degree rise
LENKERBAND	Roubaix S-Wrap
SATTEL	Body Geometry Power Sport
SATTELSTÜTZE	Carbon, single-bolt, 27.2mm
BREMSE VORNE	Shimano Tiagra BR-4770, hydraulic disc
BREMSE HINTEN	Shimano Tiagra BR-4770, hydraulic disc
SCHALTHEBEL	Shimano Tiagra Disc 4720, 10-speed
UMWERFER	Shimano Tiagra, braze-on
SCHALTWERK	Shimano Tiagra, 10-speed
KASSETTE	Shimano Tiagra, 10-speed, 11-32t
KURBELGARNITUR	Shimano Tiagra 4700, 10-speed
KETTENBLÄTTER	50/34t
KETTE	KMC X10, 10-Speed
VORDERRAD	Axis Sport Disc
HINTERRAD	Axis Sport Disc
VORDERREIFEN	Turbo Pro, 60 TPI, folding bead, BlackBelt protection, 700x26mm
HINTERREIFEN	Turbo Pro, 60 TPI, folding bead, BlackBelt protection, 700x26mm

TARMAC DISC	44	49	52	54	56	58	61
Stack (mm)	500	514	527	544	565	591	612
Reach (mm)	365	375	380	384	395	402	408
Steuerrohrlänge (mm)	105	115	126	143	163	190	210
Steuerrohrwinkel (degrees)	70.5	71.75	72.5	73	73.5	73.5	74
Tretlagerhöhe (mm)	266	266	266	268	268	268	268
Tretlagerabsenkung (mm)	74	74	74	72	72	72	72
Nachlauf (mm)	71	63	58	58	55	55	52
Gabellänge, gesamt (mm)	363	363	363	363	363	363	363
Gabelversatz / Offset (mm)	47	47	47	44	44	44	44
Mitte Tretlager - Mitte V.-achse (mm)	571	574	577	579	591	606	613
Kettenstreben-Länge (mm)	410	410	410	410	410	410	410
Radstand (mm)	969	973	975	978	990	1005	1012
Oberrohrlänge horizontal (mm)	493	511	535	544	566	581	599
Überstandshöhe (mm)	730	740	755	775	795	826	850
Sitzrohrlänge (mm)	435	451	481	499	519	540	570
Sitzrohrwinkel (degrees)	76	75.5	74	74	73.5	73.5	73
Kurbellänge (mm)	165	165	170	172.5	172.5	175	175
Lenkerbreite (mm)	360	380	400	420	420	440	440
Vorbaulänge (mm)	70	80	90	100	100	110	110
Sattelbreite (mm)	155	155	155	143	143	143	143
Länge Sattelstütze (mm)	300	300	350	350	350	400	400

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
90620-7044	TARMAC SL6 BASE DISC	Gloss Flo Red/Metallic White Silver/Fine Silver/Tarmac Black	44
90620-7049			49
90620-7052			52
90620-7054			54
90620-7056			56
90620-7058			58
90620-7061			61